



Stationary Natural Gas/LP

Belt Drive — HEG Series

Engineered with superior cleaning power, the HEG Series easily removes tough dirt and grime.

PUMP

- Belt drive triplex piston pump with ceramic plungers
- Factory preset unloader

MOTOR

- Open drip-proof electric motor

FRAME

- Powder coated steel frame

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum 200°F (250°F/121°C outlet temperature with steam option)

COMPONENTS

- ½-inch schedule 80 pipe coil heat exchanger
- Polyethylene float tank with in-line screen filter, 4-gallon
- Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 10-inch stack
- 10-inch draft diverter
- Thermal relief valve
- Electronic ignition with standing pilot light
- Pressure switch and over-pressure safety controls
- 24V control system
- Programmable logic controller (PLC) with auto start/stop and timed lockout
- Adjustable high pressure detergent injector
- Adjustable thermostat



HEG-3004-1E2G

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25°, 40° and fixed detergent nozzle
- 50-foot x ⅜-inch steel wire-braided high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTY

- Electric motor

CERTIFICATION

- ETL Certified – US and Canada

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	NATURAL GAS BTU PER HOUR	LP GAS BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.	LIST PRICE
HEG-1805-1E2G	1800	4.7	6.0 HP, 230V, 10, 25.5A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,600.00
HEG-1805-1E3G	1800	4.7	6.0 HP, 230V, 30, 16.0A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,600.00
HEG-1805-1E4G	1800	4.7	6.0 HP, 460V, 30, 8.0A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,600.00
HEG-1805-1E8G	1800	4.7	6.0 HP, 208V, 10, 28.2A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,800.00
HEG-1805-1E9G	1800	4.7	6.0 HP, 208V, 30, 18.5A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,800.00
HEG-2004-1E2G	2000	4.2	6.0 HP, 230V, 10, 25.5A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,600.00
HEG-2004-1E3G	2000	4.2	6.0 HP, 230V, 30, 16.0A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,400.00
HEG-2004-1E4G	2000	4.2	6.0 HP, 460V, 30, 8.0A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,400.00
HEG-2004-1E8G	2000	4.2	6.0 HP, 208V, 10, 28.2A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,700.00
HEG-2004-1E9G	2000	4.2	6.0 HP, 208V, 30, 18.5A	General	338,000	326,000	56.5x29x49.75	844 lb.	724 lb.	\$12,700.00
HEG-3004-1E2G	3000	3.9	8.0 HP, 230V, 10, 37.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,200.00
HEG-3004-1E3G	3000	3.9	8.0 HP, 230V, 30, 20.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$12,800.00
HEG-3004-1E4G	3000	3.9	8.0 HP, 460V, 30, 10.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$12,800.00
HEG-3004-1E5G	3000	3.9	8.0 HP, 575V, 30, 8.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,000.00
HEG-3004-1E8G	3000	3.9	8.0 HP, 208V, 10, 40.5A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,200.00
HEG-3004-1E9G	3000	3.9	8.0 HP, 208V, 30, 23.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$12,800.00
HEG-3005-1E2G	3000	4.8	10.0 HP, 230V, 10, 44.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,800.00
HEG-3005-1E3G	3000	4.8	10.0 HP, 230V, 30, 25.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,000.00
HEG-3005-1E4G	3000	4.8	10.0 HP, 460V, 30, 12.5A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,000.00
HEG-3005-1E5G	3000	4.8	10.0 HP, 575V, 30, 10.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,600.00
HEG-3005-1E8G	3000	4.8	10.0 HP, 208V, 10, 48.7A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,600.00
HEG-3005-1E9G	3000	4.8	10.0 HP, 208V, 30, 29.0A	General	338,000	326,000	56.5x29x49.75	878 lb.	758 lb.	\$13,200.00

Stationary Natural Gas/LP

Hot Water – Belt Drive – HEG Series

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS	LIST PRICE
32-1410	Additional wireless remote – Includes pump, heat and detergent buttons, requires HX-0316 or 850-0472	All models	\$645.35
850-0470	First remote, plastic control box field install kit – Includes junction box and (1) control box with pump, heat and detergent switches	All models	\$1,308.40
850-0471	First remote, metal control box field install kit – Includes junction box and (1) control box with pump, heat and detergent switches	All models	\$2,397.60
850-0472	Wireless remote field install kit – Includes receiver and (1) transmitter with pump, heat and detergent buttons	All models	\$2,768.50
850-0473	Detergent solenoid field install kit – Adds solenoid and switch to easily control the chemical injection	All models	\$439.55
850-0474	Additional programmable logic controller remotes, plastic control box field install kit – Adds additional remotes to PLC, requires HX-0314 or 850-0470	All models	\$471.30
850-0475	Additional programmable logic controller remotes, metal control box field install kit – Adds additional remotes to PLC, requires HX-0315 or 850-0471	All models	\$1,612.35
AW-0013-0278	Remote bracket with locking key – Bracket mounts to a wall or structure to securely hold the wireless remote; includes locking key to prevent theft	All models	C/F

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS	LIST PRICE
HX-0105	Liquid propane (vapor only) – Converts natural gas pressure washer to operate on liquid propane (vapor only)	All models	\$142.00
HX-0113	Dual gun – Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HEG-1805 models	\$652.00
HX-0114	Dual gun – Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HEG-3005 models	\$766.00
HX-0116	Stainless-steel coil wrap – Converts powder coated painted coil wrap to stainless-steel material	All models	\$460.00
HX-0119+	250°F steam – Increases outlet temperature to 250°F while lowering system pressure; adds re-sized 25° nozzle to be used as steam nozzle	HEG-1805 models	\$276.00
HX-0120	250°F steam – Increases outlet temperature to 250°F while lowering system pressure; adds re-sized 25° nozzle to be used as steam nozzle	HEG-2004 models	\$276.00
HX-0121	250°F steam – Increases outlet temperature to 250°F while lowering system pressure; adds re-sized 25° nozzle to be used as steam nozzle	HEG-3004 models	\$276.00
HX-0122^	250°F steam – Increases outlet temperature to 250°F while lowering system pressure; adds re-sized 25° nozzle to be used as steam nozzle	HEG-3005 models	\$276.00
HX-0305	Additional programmable logic controller remotes, plastic control box – Adds additional remotes to PLC	All models	\$567.00
HX-0306	Additional programmable logic controller remotes, metal control box – Adds additional remotes to PLC	All models	\$1,495.00
HX-0313	All stainless-steel frame and hardware – Converts powder coated painted frame and hardware to stainless-steel material	All models	\$2,640.00
HX-0314	First remote, plastic control box – Includes junction box and (1) control box with pump, heat and detergent switches	All models	\$1,090.00
HX-0315	First remote, metal control box – Includes junction box and (1) control box with pump, heat and detergent switches	All models	\$1,900.00
HX-0316	Wireless remote – Includes receiver and (1) transmitter with pump, heat and detergent buttons	All models	\$1,830.00
HX-0317	Additional wireless remote – Includes pump, heat and detergent buttons	All models	\$470.00
HX-0319	Stainless-steel access panels – Converts powder coated painted access panels to stainless-steel material	All models	\$220.00
HX-0320	Painted box kit – Adds painted side and end panels	All models	\$730.00
HX-0321	Detergent solenoid – Adds solenoid and switch to easily control the chemical injection	All models	\$310.00

+HX-0119 cannot be combined with HX-0114.

^HX-0122 cannot be combine with HX-0114.

INSTALLATION RECOMMENDATION:

This pressure washer must have a clearance of 2-feet on all sides and 4-feet above the unit.

Gas Supply Line:

Natural Gas

7- to 8-inch water column input

LP Gas

12- to 14-inch water column input

Recommended Pipe Sizes for Gas Supply Line:

Distance to Unit from Regulator		
0-feet to 50-feet	50-feet to 100-feet	100-feet to 200-feet
Natural Gas pipe size	1½-inch IPS	2-inch IPS
LP Gas pipe size	1½-inch IPS	1½-inch IPS



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.