



Premium Series

Dealer Cold Water Pressure Washers

Electric — Stationary — Belt Drive



DC-2004-WSE2G

Food and beverage industries use this stationary series to keep floors, worktables and appliances spotless. It is also a great addition to any wash bay.

PUMP

- Forged brass manifold
- Factory preset stainless-steel and brass unloader
- Thermal relief valve
- Quick connect low pressure detergent injector
- Pump accepts incoming water up to 165°F

MOTOR

- Open drip-proof electric motor with manual thermal overload protection
- 4-foot power cord with GFCI

FRAME

- Stainless-steel cabinet design with removable panel
- Four rubber isolators

COMPONENT

- Time delay shutdown

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch high pressure black hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- ETL Certified – US



Premium Series

Cold Water – Electric – Stationary – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-1003-WSE1G	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	General	NEMA 5-20P	29.5x20.5x15in.	222 lb.	172 lb.
DC-2004-WSE2G [^]	2000	3.9	6.0 HP, 230V, 1Ø, 25.5A	General	NEMA 6-30P	29.5x20.5x15in.	272 lb.	214 lb.
DC-2004-WSE3G ^{^*}	2000	3.9	6.0 HP, 230V, 3Ø, 17.3A	General	NEMA L15-20P	29.5x20.5x15in.	262 lb.	204 lb.
DC-3004-WSE2G	3000	3.9	8.0 HP, 230V, 1Ø, 37.0A	General	NEMA 6-50P	29.5x20.5x15in.	359 lb.	301 lb.
DC-3004-WSE3G [*]	3000	3.9	8.0 HP, 230V, 3Ø, 20.6A	General	NEMA L15-30P	29.5x20.5x15in.	292 lb.	234 lb.
DC-3005-WSE3G [*]	3000	4.8	10.0 HP, 230V, 3Ø, 26.2A	General	NEMA L15-30P	29.5x20.5x15in.	297 lb.	241 lb.

[^]208V motors available as options.
^{*}460V motors available as options.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
852-0208	Dual unit kit – For adding a second unit on floor stand, AW-9502-0001; includes isolators and hardware	All models
AW-9501-0000	Stainless-steel wall-mounting bracket – Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	Powder coated steel wall-mounting bracket, front-mount – Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0001	Powder coated steel floor stand; can be modified to hold up to 2 units – Provides a permanent location for your pressure washer in a shop or plant facility; 852-0208, dual unit kit, is required when a second unit is being utilized	All models
AW-9502-0003	Powder coated steel wall-mounting bracket, side-mount – Provides a permanent location for your pressure washer in a shop or plant facility	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0069	Auto start/stop – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
CX-0076	460V on 6.0-HP, 3Ø model – When 460V of power is available	DC-2004-WSE3G
CX-0077	460V on 8.0-HP, 3Ø model – When 460V of power is available	DC-3004-WSE3G
CX-0078	Remote box – Adds plastic control box with rocker switches, can be mounted away from unit to control on/off	All models
CX-0096	Hour meter – Displays the number of hours unit has been in operation	All models
CX-0109	Additional remotes, up to 3 qty. – Additional plastic control boxes with rockers, can be added to unit after the first remote is installed; requires remote box option, CX-0078	All models
CX-0114	Remote box – Adds metal control box with push-buttons, can be mounted away from unit to control on/off	All models
CX-0115	Additional remotes, up to 3 qty. – Additional metal control boxes with push-buttons, can be added to unit after the first remote is installed; Requires remote box option, CX-0114	All models
CX-0119	208V on 6.0-HP, 1Ø model – When 208V of power is available	DC-2004-WSE2G
CX-0120	208V on 6.0-HP, 3Ø model – When 208V of power is available	DC-2004-WSE3G
CX-0121	460V on 10.0-HP, 3Ø model – When 460V of power is available	DC-3005-WSE3G
CX-0122 [*]	Wheel kit with 4 flat-free tires – Allows the unit to become portable	2.0 HP, 1Ø & 8.0 HP, 1Ø models
CX-0123 [*]	Wheel kit with 4 flat-free tires – Allows the unit to become portable	6.0 HP, 1Ø models
CX-0124 [*]	Wheel kit with 4 flat-free tires – Allows the unit to become portable	6.0 HP, 3Ø & 8.0 HP, 460V models
CX-0125 [*]	Wheel kit with 4 flat-free tires – Allows the unit to become portable	8.0 HP, 230V, 3Ø models
CX-0126 [*]	Wheel kit with 4 flat-free tires – Allows the unit to become portable	10.0 HP models

^{*}Replaces the standard 4-foot power cord with a 35-foot power cord.



DC-2004-WSE2G shown with stainless-steel wall-mounting bracket, AW-9501-0000



Powder coated steel floor stand, AW-9502-0001



NEMA 5-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.