



BELT DRIVE • ELECTRIC POWERED • COLD WATER



5-YEAR LIMITED WARRANTY • CERTIFIED TO UL SAFETY STANDARDS • ISO-9001 COMPANY













Tri-lingual labels:

Operating instruc-

tions in English,

Spanish and

French.

Discover the Many Reasons LANDA is the Only Pressure Washer Built to Last!

Straight-Through

insulated wrap for

Wand: Stainless

steel wand with

point-and-shoot

effectiveness.

Spring-loaded Trigger Gun: For safe control of high pressure spray and convenience of remote operation.

Swivel Swedge Fitting: For tanglefree handling of hose and trigger gun.

24" Safety Hose Guard: Gives strain relief to hose connection and diverts any spray from operator in the event of hose failure.

Hose Hanger: For convenient carrying and access to hose.

Quality Unloader: Durable pressure-trapping unloader diverts water flow when trigger gun is not in use.

Tri-plunger Pump:

Oil-bath, forged brass head pump has 5-year limited warranty on oilend of pump, lifetime warranty on pump head.

High-Pressure Hose: 50 ft. of 3/8" wire braid hose with quick coupler rated for up to 5800 psi.

Thermal-Pump Protector: Protects pump from overheating in bypass (not visible). **1.25" Chrome-Plated Handle and Bumper:** To assist in lifting and moving.

Certified to UL-1776 Standards

> **Spring-Loaded Feet:** Absorb vibration and keep washer from "walking."

Chemical Injector: For lowpressure application of soap.

DISTRIBUTED BY:

Industrial Strength Motor: With full service factor and solid performance record.

Quick-Release Nozzles: Conveniently mounted and color-coded for easy selection of spray nozzles (0°, 15°, 25°, 40°) and soap nozzle.

Electrical Box: Water resistant for added safety and positioned for easy servicing.

High-Impact Belt Guard: For protection and operator safety.

Belt Pulley System: Notched V-belts and cast iron pulleys reduce belt slippage and offer longer belt life with cooler operation (*not visible*).

Electrical Cord: 36 ft. for added mobility; with GFCI (on single-phase models, 30 amps or less).

Tubed Pneumatic Tires: For all-terrain maneuvering and absorbing shock and vibration.

Heavy-Duty Chassis: Made of 10-gauge steel with fully welded seams and powder-coat epoxy finish to prevent rusting.

Brass, Steel and JIC fittings: Easy to service and corrosion-resistant.

PE SPECIFICATIONS

MODEL PART NUMBER		PE3-11021D	PE4-20021A,B,C	PE4-30021A,B,C	PE5-30021A,B,C
DISCHARGE	GPM (LPM)	2.8 (10.6)	4.2 (15.9)	3.5 (13.2)	4.8 (18.2)
OPERATING PRESSURE	PSI (Bar)	1000 (69)	2000 (138)	3000 (207)	3000 (207)
MOTOR	HP	2	6	7.5	10
	Volts/Phase	120V/1ph	230V/1ph, 230V/3ph, 460V/3ph	230V/1ph, 230V/3ph, 460V/3ph	230V/1ph, 230V/3ph, 460V/3ph
	Amps	18	27, 16, 8	36, 21.5, 10.5	45, 27, 14
CORD & PLUG		36' GFCI, 20 Amp Plug	36' GFCI, 15' Cord, 15' Cord; No Plug	15' Cord, No Plug	15' Cord, No Plug
PUMP		Tri-Plunger, Oil Bath			
PAINT		Electrostatically Applied Epoxy Powder Coating			
HOSE		3/8" I.D. x 50', 5800 PSI In:	sulated Wire Braid with Quick Coupler		
GUN		Insulated Shut-Off			
WAND		Stainless Steel Straight Th	ru		
NOZZLES		0°, 15°, 25°, 40°			
BELT GUARD Totally Enclosed (Complies with OSHA Guidelines)					
WHEELS		2 Ply Tubed Pneumatic			
LENGTH/WIDTH/HEIGHT		33" x 27" x 24" (84cm x 69	0cm x 61cm)		38" x 30" x 21" (97cm x 76cm x 53cm)
SHIPPING WEIGHT	Lbs (Kg)	195 <i>(88)</i>	270, 220, 220 (122, 100, 100)	290, 270, 270 (132, 122, 122)	290 (132)

Note: We are constantly improving and updating our products. Consequently, pictures, features and specifications in this brochure may differ slightly from current models. There may be slight variances in gallonage and pressures due to variances allowed by manufacturers of our machine components. We attempt to keep our machines performance ±5% of listed specifications. For indoor/outdoor use. Customer is responsible for any permits, compliance with codes, or other government requirements associated with the installation, use, or disposal of waste associated with this equipment.





FORM #96-007 • 7/99 • LANDA, INC. • 4275 NW Pacific Rim Blvd., Camas, Washington 98607 USA