

# **Aluminum Series**

Dealer Cold Water Pressure Washers



This aluminum series is built with longevity in mind. It delivers high performance for prepping surfaces and blasting away muck and grime on a routine basis.

#### PUMP

- Equipped with Mi-T-M Pressure Relief Start
- External bypass system protects from heat build-up
- Stainless-steel and brass trapping unloader
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### FRAME

- Lightweight, corrosion-resistant aluminum frame and base plate with 1<sup>1</sup>/<sub>4</sub>-inch tube handles
- Patented vibration isolation plate with four rubber isolators
- Two-piece belt guard
- 13-inch flat-free tires

#### UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- External downstream detergent injector with detergent nozzle
- 50-foot x 3%-inch non-marking high pressure hose
- 48-inch lance with rubber grip
- Professional-grade insulated "easy pull" trigger gun with safety lock-off

#### LIMITED WARRANTY

• 3 year engine

#### CERTIFICATION

• ETL Certified – US (Select models, see chart on back)



## **Aluminum Series** Cold Water - Gasoline - Portable - Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-3504-BA0H6G*	3500	3.7	389cc Honda GX390 OHV+	General	46.5x28x27.5in.	215 lb.	165 lb.
DC-3504-BA0K6G*	3500	3.7	429cc Kohler CH440 OHV	General	46.5x28x27.5in.	237 lb.	173 lb.
DC-3504-BA0H6A*	3500	3.7	389cc Honda GX390 OHV+	AR	46.5x28x27.5in.	215 lb.	165 lb.
DC-3504-BA0K6A*	3500	3.7	429cc Kohler CH440 OHV	AR	46.5x28x27.5in.	219 lb.	155 lb.
DC-3504-BA0M6A	3500	3.7	420cc Mi-T-M OHV	AR	46.5x28x27.5in.	215 lb.	165 lb.
DC-4004-BA0H6G*	4000	3.5	389cc Honda GX390 OHV+	General	46.5x28x27.5in.	223 lb.	159 lb.
DC-4004-BA0K6G*	4000	3.5	429cc Kohler CH440 OHV	General	46.5x28x27.5in.	219 lb.	173 lb.
DC-4004-BA0H6A*	4000	3.5	389cc Honda GX390 OHV+	AR	46.5x28x27.5in.	207 lb.	143 lb.
DC-4004-BA0K6A*	4000	3.5	429cc Kohler CH440 OHV	AR	46.5x28x27.5in.	215 lb.	155 lb.
DC-4004-BA0M6A	4000	3.5	420cc Mi-T-M OHV	AR	46.5x28x27.5in.	215 lb.	165 lb.
+49 state engine. Not for sale in *ETL Certified – US	n California.						

#### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS		
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up			
851-0338	50-foot x %-inch non-marking hose – For when you need extra hose for added mobility	All models		
AW-7510-0035	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated, 3.5 orifice	All models		
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models		



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.